

DATA SHEET



COMBINED SAFETY SHOWER AND EYEBATH

TYPE	MAINS FED OR TANK FED
MODEL NUMBER	FSS370 – Mains fed connection
MODEL NUMBER	FSS370T – Gravity fed connection
STANDARD	ANSI Z358.1-2014
OPERATING CONDITIONS	
PRESSURE	2 – 5 bar – Mains fed
PRESSURE – MODEL FS370ST	0.5Bar – Gravity fed
TEMPERATURE	1 deg C to + 30 deg C
TECHNICAL DETAILS	
INLET CONNECTION	1 ½” BSPF (options available)
EYEBATH DRAIN OUTLET CONNECTION	1 ½” BSPF
SHOWER FLOW RATE	76lpm
EYEBATH FLOW RATE- MAINS FED	23lpm
EYEBATH FLOW RATE- GRAVITY FED	Min 1.5lpm per nozzle
OPERATING VALVES	316 STAINLESS STEEL – stay open
SHOWER OPERATION	Pull Handle
EYEBATH OPERATION	Lever handle
MATERIAL DETAILS	
SHOWER PIPEWORK	304 STAINLESS STEEL (316 as option)
SHOWER PIPEWORK – MODEL FS370SP	304 STAINLESS STEEL (optional 316) LUMINOUS POWDER COATING
SHOWER ROSE	STAINLESS STEEL
EYEBATH BOWL	STAINLESS STEEL
OPTIONAL EXTRAS AVAILABLE IF REQUIRED	
Foot Treadle for eyebath	Remote alarms
Local alarm (flashing alarm & siren)	Pendant lamp
Powder coating	Flanged inlet & outlet



MANUFACTURERS AND SUPPLIERS OF EMERGENCY SAFETY SHOWERS AND EYEBATHS

AQUA SAFETY SHOWERS INTERNATIONAL LTD

Unit 3, Prospect Industrial Estate, Platt Lane, Hindley, Wigan, Lancashire WN2 3PA. United Kingdom.

Telephone : +44 (0) 1942 318096 Fax : +44(0) 1942 258048 Email: sales@safetyshowersinternational.com

Registered office: 56 Ormskirk Street, St Helens, WA10 2TF, UK.

Registration number: 10427026

Website: www.safetyshowersinternational.com

VAT Registration Number: 259714570