

DATA SHEET



STAINLESS SAFETY WALL MOUNTED SHOWER

TYPE	MAINS FED
MODEL NUMBER	WM150S
MODEL NUMBER	WM150SP – Mains fed connection - luminous
STANDARD	ANSI Z358.1-2014
OPERATING CONDITIONS	
PRESSURE	2 – 5 bar – Mains fed
TEMPERATURE	1 deg C to + 30 deg C
TECHNICAL DETAILS	
INLET CONNECTION	1" BSPF (options available)
SHOWER FLOW RATE	76lpm
OPERATING VALVES	316 STAINLESS STEEL – stay open
SHOWER OPERATION	Pull Handle
MATERIAL DETAILS	
SHOWER PIPEWORK	304 STAINLESS STEEL (316 as option)
SHOWER PIPEWORK – MODEL FS370SP	304 STAINLESS STEEL (optional 316) LUMINOUS POWDER COATING
SHOWER ROSE	STAINLESS STEEL
OPTIONAL EXTRAS AVAILABLE IF REQUIRED	
Remote alarm	Local alarm (flashing alarm & siren)
Pendant lamp	



MANUFACTURERS AND SUPPLIERS OF EMERGENCY SAFETY SHOWERS AND EYEBATHS

AQUA SAFETY SHOWERS INTERNATIONAL LTD

Unit 3, Prospect Industrial Estate, Platt Lane, Hindley, Wigan, Lancashire WN2 3PA. United Kingdom.

Telephone : +44 (0) 1942 318096 Fax : +44(0) 1942 258048 Email: sales@safetyshowersinternational.com

Registered office: 56 Ormskirk Street, St Helens, WA10 2TF, UK.

Registration number: 10427026

Website: www.safetyshowersinternational.com

VAT Registration Number: 259714570